



Electrical:

- 1.Voltage: 50V AC(RMS)/DC
- 2.Current: 0.5A AC(RMS)/DC
- 3.Contact Resistance: 90 mΩ max
- 4.Withstanding Voltage:
150V AC /RMS
- 5.Insulation Resistance: 500 MΩ min.
- 6.Operating Temperature: -40℃~+85℃

Material:

Housing: High temperature Plastic(UL94V-0)
Terminal:Copper Alloy

	A	B	C	D	E	F	G
30 PIN	11.2	12.4	14.3	22.6	23.2	16.65	18.0
40 PIN	15.2	16.4	18.3	26.6	27.2	20.65	22.0
50 PIN	19.2	20.4	22.3	30.6	31.2	24.65	26.0
60 PIN	23.2	24.4	26.3	34.6	35.2	28.65	30.0
70 PIN	27.2	28.4	30.3	38.6	39.2	32.65	34.0
80 PIN	31.2	32.4	34.3	42.6	43.2	36.65	38.0
90 PIN	35.2	36.4	38.3	46.6	47.2	40.65	42.0
100 PIN	39.2	40.4	42.3	50.6	51.2	44.65	46.0
110 PIN	43.2	44.4	46.3	54.6	55.2	48.65	50.0
120 PIN	47.2	48.4	50.3	58.6	59.2	52.65	54.0

UNITS:		CSCONN		CSCONN PRECISE ELECTRONICS CO.,LTD			
mm GENERAL TOLERANCE		PART NO.(INTENDED USE) CBT-0860XXF-13		TITLE: BTB 0.8MM XP FEMALE 浮动式			
X. ° ±5°	0. X±0.25	APPD:		DWG NO. BTB			
X. 1±2°	0. XX±0.2	CHKD: Skila			SCALE	SHEET	REV
XX. ±1°	0. XXX±0.1	DR: Kitty			1:1	1 OF 1	A