



- SPECIFICATIONS:**
1. Electrical Characteristics:
  2. Current Rating: 1AMP Max.
  3. Dielectric Withstanding Voltage: 500V AC For 1 Minute.
  4. Contact Resistance: 40m OHMS Max.
  5. Insulation Resistance: 1000M OHMS Min At 250V DC.
  6. Operation Temperature: -25° C~+85° C.
  7. Operating Voltage: 250V (AC/DC).

**Bill Of Materials:**

No.	TITLE	MATERIAL	FINISH(OR COLOR)	No.
1	胶芯	LCP+30%GF UL94 V-0	BLACK	1
2	铜向式-端子	COPPER ALLOY,T=0.15mm	1u" GLD PLATED	1组
3	外壳	SUS 304(12H),T=0.15mm	Solder tails area:Gold Flash,Overall Ni.50u"	1

UNITS:		CSCONN	
TTTT	GENERAL TOLERANCE	PART NO.(INTENDED USE)	TITLE:
X. ° ±5°	0. X±0.25	CST0616315001	SIM CARD 6P H=1.5MM 带档位
XX. ±1°	0. XX±0.1	APPD:	DWG NO. SIM CARD
		CHKD: Skitia	SCALE SHEET
		DR: Kitty	1 OF 1 REV
			A

**PCB LAYOUT**

CSCONN PRECISE ELECTRONICS CO.,LTD